

Eaton XTOB2P4BC1

Catalog Number: XTOB2P4BC1

Eaton XT IEC bimetallic overload relay, 1.6-2.4A overload range, 45 mm Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, used with 7-15A contactor, 10A trip type

General specifications



Product Name

Eaton XT IEC bimetallic overload relay

Catalog Number

XTOB2P4BC1

EAN

4015082784379

Product Length/Depth

3.27 in

Product Height

1.89 in

Product Width

1.77 in

Product Weight

0.7 lb

Compliances

CE Marked
ATEX Compliant
RoHS Compliant

Certifications

UL Listed
CSA Certified
IEC 60947
EN 60947

Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.

defaultTaxonomyAttributeLabel

Overload range

1.6-2.4 A

Type

XT IEC Bimetallic Overload Relay

Used with

7-15A contactor

Frame size

45 mm

Contact configuration

1 NO, 1 NC

Mounting

Direct

Trip type

10 A

Resources

Brochures

[C440 Electronic Overload Relay](#)

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTOB_BC1 AutoCAD 2D Footprint \(mm\)](#)

[XTOB_BC1 2D Drawing Xchange](#)

[XTOB_BC1 3D Model Xchange](#)

[XTOB_BC1 3D Inventor](#)

[XTOB_BC1 AutoCAD 2D Footprint](#)

[XTOB_BC1 2D PDF](#)

Multimedia

[Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained](#)

Specifications and datasheets

[Global Data Sheet - XTOB2P4BC1](#)

[Eaton Specification Sheet - XTOB2P4BC1](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)