

Eaton XTOBP60CC1

Catalog Number: XTOBP60CC1

Eaton XT IEC bimetallic overload relay, 0.4-0.6A overload range, 45 mm Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, used with 18-32A contactor, 10A trip type

General specifications



Product Name

Eaton XT IEC bimetallic overload relay

Catalog Number

XTOBP60CC1

EAN

4015082784454

Product Length/Depth

3.27 in

Product Height

1.89 in

Product Width

1.77 in

Product Weight

0.5 lb

Compliances

ATEX Compliant
RoHS Compliant
CE Marked

Certifications

UL Listed
CSA Certified
IEC 60947
EN 60947

Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.

Overload range

0.4-0.6 A

Type

XT IEC Bimetallic Overload Relay

Used with

18-32A contactor

Frame size

45 mm

Contact configuration

1 NO, 1 NC

Mounting

Direct

Trip type

10 A

Brochures

C440 Electronic Overload Relay

Catalogs

Eaton's Volume 5—Motor Control and Protection

Drawings

XTOB_CC1 3D Inventor

XTOB_CC1 2D Drawing Xchange

XTOB_CC1 3D Model Xchange

XTOB_CC1 2D PDF

XTOB_CC1 AutoCAD 2D Footprint (mm)

XTOB_CC1 AutoCAD 2D Footprint

Multimedia

Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained

Specifications and datasheets

Global Data Sheet - XTOBP60CC1

Eaton Specification Sheet - XTOBP60CC1



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia