ScrubShield®
Complies with UL514A

| Description | Catalog Number | Description | Catalog Number | Description | Catalog Number |
|---|---|---|---|---|---|
| **Style Line® Decorator/GFCI**<br>(2) Style Line decorator openings for power and/or datacom applications. | <br>S1SP | **Duplex/Duplex**<br>(2) Duplex openings for power and/or datacom applications. | <br>S1SPDU | **Duplex/Style Line Decorator**<br>(1) Duplex and (1) Style Line decorator opening for power and/or datacom applications. | <br>S1SPDUSL |
| **Hubbell 4 X 4**<br>(4) 20A, 125V receptacles; (4) Keystone openings for Hubbell jacks or flush AV connectors; Power can be wired as single or two circuit with isolated ground capability. Includes ⏻ stickers;<br>Provided with 15 ft. wire leads<br>Provided with 30 ft. wire leads. | <br>S1SP4X4<br>S1SP4X4C<br>S1SP4X415<br>S1SP4X430 | **Carpet Furniture Feed Cover/Flange***<br>(1) 3/4" and (1) 1-1/2" NPT access holes for power and/or datacom applications; Universal Cover not required. Includes carpet flange.<br>Aluminum Fin.<br>Brass Finish<br>Black<br>Gray | <br>S1SPFFAL<br>S1SPFFBRS<br>S1SPFFBL<br>S1SPFFGY | **Tile Furniture Feed Cover/Flange***<br>(1) 3/4" and (1) 1-1/2" NPT access holes for power and/or datacom applications; Universal Cover not required. Includes tile flange.<br>Aluminum Fin.<br>Brass Finish<br>Black<br>Gray | <br>S1SPFFTAL<br>S1SPFFTBRS<br>S1SPFFTBL<br>S1SPFFTGY |
| **Single Receptacle + Data**<br>Opening for 20 or 30A Twist-Lock® receptacle (1.56" OD) and (2) Keystone openings for Hubbell jacks or flush AV connectors. | <br>S1SPTL | **Hubbell DataCom + Power**<br>(1) 20A, 125V receptacle and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications; marked with "⏻ Controlled". | <br>S1SP3IM<br>S1SP3IMC | **Hubbell DataCom + Duplex**<br>(1) Duplex opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications. | <br>S1SPDU2IM |
| **Hubbell DataCom + Style Line Decorator**<br>(1) Style Line decorator opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications. | <br>S1SPSL2IM | **Hubbell DataCom**<br>1 unit flush Hubbell iSTATION opening and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications. | <br>S1SP4IM | **Active Multimedia + Power**<br>Single 20A, 125V receptacle; (2) flush Keystone openings; (1) rectangular Style Line decorator opening to accommodate active multimedia modules or low voltage outlet frames. marked with "⏻ Controlled". | <br>S1SPAMM20<br>S1SPAMM20C |
| **Extron® or FSR + Power**<br>(1) 20A, 125V receptacle. Recessed opening for (3) single Extron MAAP series adapter plates or FSR IPS plates. marked with "⏻ Controlled". | <br>S1SPEXT1<br>S1SPEXT1C | **Extron or FSR + Power**<br>(1) 20A, 125V receptacle; Recessed opening for (1) single Extron MAAP and (2) single AAP series adapter plates or FSR IPS plates. marked with "⏻ Controlled". | <br>S1SPEXT2<br>S1SPEXT2C | **Extron or FSR Single-Service**<br>Recessed opening for (2) single Extron MAAP and (2) single AAP series adapter plates or FSR IPS plates. | <br>S1SPEXT3 |
| **Extron AAP + Power**<br>(1) 20A, 125V receptacle; (2) flush Keystone & recessed opening for (2) single Extron AAP Series adapter plates. marked with "⏻ Controlled". | <br>S1SPEXT4<br>S1SPEXT4C | **Ortronics Series II® + Power**<br>(1) 20A, 125V receptacle; Recessed opening for (3) 1 unit Ortronics Series II modules. marked with "⏻ Controlled". | <br>S1SPORT<br>S1SPORTC | **Ortronics TracJack® + Power**<br>(1) 20A, 125V receptacle; Recessed bezel for (6) Ortronics TracJack modules; marked with "⏻ Controlled" | <br>S1SPTRAC<br>S1SPTRACC |
| **Panduit Mini Com® 4 X 4**<br>(4) 20A, 125V receptacles; (4) Openings for Panduit Mini-Com Connectivity. Includes ⏻ stickers. | <br>S1SP4X4PA<br>S1SP4X4PAC | **SYSTIMAX® 4 X 4**<br>(4) 20A, 125V receptacles; (4) Openings for SYSTIMAX Connectivity. Includes ⏻ stickers. | <br>S1SP4X4SYS<br>S1SP4X4SYSC | **Siemon MAX® + Power**<br>(1) 20A, 125V receptacle; Recessed bezel for (6) Siemon MAX modules. marked with "⏻ Controlled". | <br>S1SPMAX<br>S1SPMAXC |

*Note: *Furnished with two screw-in flexible metal conduit connectors. See Network Wiring section for complete offering of Hubbell jacks, frames and datacom accessories. See page R-30 for FRPT Configuration Chart.*

## Sub-Plate Accessories

| Description | | |
|---|---|---|
| Replacement Threaded Conduit Plugs Used with S1SPFFx and S1SPFFTx only. Sub-Plate is supplied with plugs. | | |
| **Color** | **1-1/2" Plug** | **3/4" Plug** |
| Aluminum Finish | S1FP15AL | S1FP34AL |
| Brass Finish | S1FP15BRS | S1FP34BRS |
| Black | S1FP15BL | S1FP34BL |
| Gray | S1FP15GY | S1FP34GY |



| Description | Catalog Number |
|---|---|
| Replacement for S1SPMAX. Sub-Plate is supplied with data frame. Works with Siemon MAX®. | S1DFMAX |
| Replacement for S1SPTRAC Sub-Plate. Sub-Plate is supplied with data frame. Works with Ortronics TracJack. | S1DFTRAC |
| Blank Style Line decorator frame, Black.<br>2-Port Style Line decorator frame, Black.<br>4-Port Style Line decorator frame, Black.<br>6-Port Style Line decorator frame, Black. | NS620BK<br>NS612BK<br>NS614BK<br>NS616BK |



*Extron® is a registered trademark of Extron Electronics. MAX® is a registered trademark of The Siemon Company. Mini-Com® and Panduit® are registered trademarks of Panduit Corp. SYSTIMAX® is a registered trademark of CommScope, Inc. TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.*

*Dimensions in Inches (mm)*