SystemOne Flush Sub-Plates

ScrubShield® c UL us
Complies with UL514A

Description	Catalog Number	Description	Catalog Number	Description	Catalog Number
Style Line® Decorator/GFCI (2) Style Line® decorator openings for power and/or datacom applications. ③ Non-Metallic ③.⑤ Metal	 **S1SP**	**Duplex/Duplex** (2) Duplex openings for power and/or datacom applications. ③ Non-Metallic ③.⑤ Metal	 **S1SPDU**	**Duplex/Style Line® Decorator** (1) Duplex and (1) Style Line® decorator opening for power and/or datacom applications. ③ Non-Metallic ③.⑤ Metal	 **S1SPDUSL**
Hubbell 4 X 4 (4) 20A, 125V receptacles. (4) Keystone openings for Hubbell jacks or flush AV connectors. Power can be wired as single or two circuit with isolated ground capability. ④ Includes ⏻ stickers. Provided with 15 ft. wire leads Provided with 30 ft. wire leads	 **S1SP4X4** **S1SP4X4C** **S1SP4X415** **S1SP4X430**	**Carpet Furniture Feed Cover/Flange*** (1) 3/4" and (1) 1-1/2" NPT access holes for power and/or datacom applications. Universal Cover not required. Includes carpet flange. ③ Non-Metallic — Aluminum Fin. ③.⑤ Metal — Brass Finish, Black, Gray	 **S1SPFFAL** **S1SPFFBRS** **S1SPFFBL** **S1SPFFGY**	**Tile Furniture Feed Cover/Flange*** (1) 3/4" and (1) 1-1/2" NPT access holes for power and/or datacom applications. Universal Cover not required. Includes tile flange. ③ Non-Metallic — Aluminum Fin. ③.⑤ Metal — Brass Finish, Black, Gray	 **S1SPFFTAL** **S1SPFFTBRS** **S1SPFFTBL** **S1SPFFTGY**
Single Receptacle + Data Opening for 20 or 30A Twist-Lock® receptacle (1.56" OD) and (2) Keystone openings for Hubbell jacks or flush AV connectors. ④	 **S1SPTL**	**Hubbell DataCom + Power** (1) 20A, 125V receptacle and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications. ⑤ Marked with "⏻ Controlled"	 **S1SP3IM** **S1SP3IMC**	**Hubbell DataCom + Duplex** (1) Duplex opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications. ⑤	 **S1SPDU2IM**
Hubbell DataCom + Style Line® Decorator (1) Style Line® decorator opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications. ⑤	 **S1SPSL2IM**	**Hubbell DataCom** 1 unit flush Hubbell iSTATION opening and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications. ③.⑤	 **S1SP4IM**	**Active Multimedia + Power** Single 20A, 125V receptacle; (2) flush Keystone openings; (1) rectangular Style Line® decorator opening to accommodate active multimedia modules or low voltage outlet frames. ⑤ Marked with "⏻ Controlled"	 **S1SPAMM20** **S1SPAMM20C**
Extron® or FSR + Power (1) 20A, 125V receptacle. Recessed opening for (3) single Extron® MAAP series adapter plates or FSR IPS plates. ④Marked with "⏻ Controlled"	 **S1SPEXT1** **S1SPEXT1C**	**Extron® or FSR + Power** (1) 20A, 125V receptacle. Recessed opening for (1) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates. ④Marked with "⏻ Controlled"	 **S1SPEXT2** **S1SPEXT2C**	**Extron® or FSR Single-Service** Recessed opening for (2) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates. ④.⑤	 **S1SPEXT3**
Extron® AAP + Power (1) 20A, 125V receptacle. (2) flush Keystone & recessed opening for (2) single Extron® AAP Series adapter plates. ④Marked with "⏻ Controlled"	 **S1SPEXT4** **S1SPEXT4C**	**Ortronics Series II® + Power** (1) 20A, 125V receptacle. Recessed opening for (3) 1 unit Ortronics Series II® modules. ⑤Marked with "⏻ Controlled"	 **S1SPORT** **S1SPORTC**	**Ortronics TracJack® + Power** (1) 20A, 125V receptacle. Recessed bezel for (6) Ortronics TracJack® modules. ⑤ Marked with "⏻ Controlled"	 **S1SPTRAC** **S1SPTRACC**
Panduit Mini Com® 4 X 4 (4) 20A, 125V receptacles. (4) Openings for Panduit Mini-Com Connectivity. ④ Includes ⏻ stickers.	 **S1SP4X4PA** **S1SP4X4PAC**	**SYSTIMAX® 4 X 4** (4) 20A, 125V receptacles. (4) Openings for SYSTIMAX® Connectivity. ④ Includes ⏻ stickers.	 **S1SP4X4SYS** **S1SP4X4SYSC**	**Siemon MAX® + Power** (1) 20A, 125V receptacle. Recessed bezel for (6) Siemon MAX® modules. ⑤ Marked with "⏻ Controlled"	 **S1SPMAX** **S1SPMAXC**

*Note: *Furnished with two screw-in flexible metal conduit connectors.*
⊖ Signifies minimum depth of concrete pour in inches for Metal Floor Boxes (S1CFB, S1SFB and S1SFBAV) and Non-Metallic Floor Box (S1PFB).

Sub-Plate Accessories

Description		
Replacement Threaded Conduit Plugs Used with S1SPFFx and S1SPFFTx only. Sub-Plate is supplied with plugs.		
Color	**1-1/2" Plug**	**3/4" Plug**
Aluminum finish	**S1FP15AL**	**S1FP34AL**
Brass finish	**S1FP15BRS**	**S1FP34BRS**
Black	**S1FP15BL**	**S1FP34BL**
Gray	**S1FP15GY**	**S1FP34GY**



Description	Catalog Number
Replacement for S1SPMAX. Sub-Plate is supplied with data frame. Works with Siemon MAX®.	**S1DFMAX**
Replacement for S1SPTRAC Sub-Plate. Sub-Plate is supplied with data frame. Works with Ortronics TracJack®.	**S1DFTRAC**
Blank Style Line® decorator frame, black. 2-Port Style Line® decorator frame, black. 4-Port Style Line® decorator frame, black. 6-Port Style Line® decorator frame, black.	**NS620BK** **NS612BK** **NS614BK** **NS616BK**



Dimensions in Inches (mm)

Extron® is a registered trademark of Extron Electronics. MAX® is a registered trademark of The Siemon Company. Mini-Com® and Panduit® are registered trademarks of Panduit Corp. SYSTIMAX® is a registered trademark of CommScope, Inc. TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.