

HBL2000 and HBL2000A Series

| | Description | Color | Catalog Number | | Description | Color | Catalog Number |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|---------------------------------------------------------------------------------------------------------|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-----------------------------------------------------------------------------------------------------------|
| HBL2000 Series | Base and Cover (300V Rated) Cover is 0.025 in. (0.635) thick up to 300V AC applications. Packed 50 ft. (15m) per carton, 5 ft. (1.5m) lengths. | Ivory Gray | HBL2000BCIV HBL2000BCGY A: 60.00" (1,524.00) B: 1.31" (33.27) C: .83" (21.08) | HBL2000A Series | Base and Cover (600V Rated) Cover is 0.040 in. (1.016) thick up to 600V AC or higher capacity power applications (up to 26 #12AWG wires). Packed 50 ft. (15m) per carton, 5 ft. (1.5m) lengths. | Ivory Gray | HBL2000BCAIV HBL2000BCAGY A: 60.00" (1,524.00) B: 1.31" (33.27) C: .83" (21.08) |
| | | | | | | | |

| | Description | Color | Catalog Number | Description | Color | Catalog Number |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------------------------------------------|
| Base and Cover | 5 Ft. Base Only For use with HBL2000 and HBL2000A raceway. Packed 50 ft. (15m) per carton, 5 ft. (1.5m) lengths. | Ivory Gray | HBL2000B5IV HBL2000B5GY A: 60.00" (1,524.00) B: 1.31" (33.27) | 5 Ft. Cover Only (300V Rated) Cover is 0.025 in. (0.635) thick. Packed 50 ft. (15m) per carton, 5 ft. (1.5m) lengths. | Ivory Gray | HBL2000CIV HBL2000CGY A: 60.00" (1,524.00) B: 1.31" (33.27) |
| | | | | 5 Ft. Cover Only (600V Rated) Cover is 0.040 in. (1.016) thick up to 600V AC or higher capacity power applications (up to 26 #12AWG wires). Packed 50 ft. (15m) per carton, 5 ft. (1.5m) lengths. | Ivory Gray | HBL2000CAIV HBL2000CAGY A: 60.00" (1,524.00) B: 1.31" (33.27) |
| | | | | | | |

| | Description | Color | Catalog Number | Description | Color | Catalog Number |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|---------------|---------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|---------------|------------------------------------------------------------------------------------------------------|
| Device Boxes | 1-Gang Device Box For deep switches and receptacles. Base has one ½ in. trade size KO and rectangular KO for extension to wall box. | Ivory Gray | HBL2048IV HBL2048GY A: 4.54" (115.32) B: 2.82" (71.63) C: 1.75" (44.45) | 2-Gang Device Box For deep switches and receptacles. Base has one ½ in. trade size KO and rectangular KO for extension to wall box. | Ivory Gray | HBL20482IV HBL20482GY A: 4.54" (115.32) B: 4.64" (117.86) C: 1.75" (44.45) |
| | | | | | | |

| | | | |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------------------------------------------|
| Elbows | Internal Elbow Bend Radius For inside surface at right angles requiring a 1.5" (38.10) bend radius. Suitable for Category 5, 5e, 6 and 6A applications. | Ivory Gray | HBL2017BRIV* HBL2017BRGY* A: .85" (21.56) B: 3.47" (88.11) |
| | | | |
| | External Elbow Bend Radius For outside surfaces at right angles requiring a 1.5 in. (38.10) bend radius. Suitable for Category 5, 5e, 6 and 6A applications. | Ivory Gray | HBL2018BRIV* HBL2018BRGY* A: 5.11" (129.72) |
| | | | |
| | Flat Elbow Bend Radius For branches at right angles requiring a 1.5 in. (38.10) bend radius. Suitable for Category 5, 5e, 6 and 6A applications. | Ivory Gray | HBL2011BRIV* HBL2011BRGY* A: 4.29" (109.03) |
| | | | |
| Tees | Tee Fitting Bend Radius For branches at right angles. Couplings furnished. Suitable for Category 5, 5e, 6 and 6A applications. | Ivory Gray | HBL2015BRIV* HBL2015BRGY* A: 7.35" (186.78) B: 4.33" (110.00) |
| | | | |

Note: *HBL2001C couplings included.

**Galvanized Steel.

Dimensions in Inches (mm)