



Fed. Spec.

Meets UL Standard 943
Class A GFCI

Features and Benefits

Extra Heavy Duty Industrial and Hospital Grade GFCI Receptacles Tamper-Resistant and Weather Resistant

10kA Short Circuit Current Rating

Limits improper access to energized contacts

- Exclusive patented tamper-resistant protection through switching technology
- Continually tests and monitors for people protection automatically
- Patented self test diagnostics

Power indication

- Steady "ON" **GREEN LED** provides indication of power

Ground fault indicator

- Steady "ON" **RED LED** provides visual indication of a ground fault condition; flashing red indicates device has lost capability to provide protection

No power at face if reverse wired

- Open circuit condition eliminates false assumption of protection at face

Durable face with V-0 flammability rating

- Polyester face cover



AUTOGUARD® Self Test GFCI Receptacles Tamper-Resistant and Weather Resistant



Description	Rating	Color	Standard	Hospital Grade
Flush, polyester face, back and side wired, multiple drive screws.		Black	GFR5262SGBK	GFR8200SGBK
		Brown	GFR5262SG	GFR8200SG
		Gray	GFR5262SGGY	GFR8200SGGY
		Ivory	GFR5262SGI	GFR8200SGI
		Red	GFR5262SGR	GFR8200SGR
		White	GFR5262SGW	GFR8200SGW
Flush, polyester face, back and side wired, multiple drive screws.		Black	GFR5362SGBK	GFR8300SGBK
		Brown	GFR5362SG	GFR8300SG
		Gray	GFR5362SGGY	GFR8300SGGY
		Ivory	GFR5362SGI	GFR8300SGI
		Red	GFR5362SGR	GFR8300SGR
		White	GFR5362SGW	GFR8300SGW

Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles listed above are furnished with both a matching color nylon wallplate, and a SS26 302/304 super stainless steel wallplate. 20 amp feed-through capability.
See page Tech-10 for Tamper-Resistant and Weather Resistant descriptions.

GFCI Receptacle Specifications per GFCI Products Listed (Pages L-3 to L-8)

Trip Level	4 to 6 mA.
Trip Time	.025 second nominal.
Frequency	60 Hz.
Voltage	120V AC +10% - 15% (102V to 132V).
Amperage	15A/20A, 20A Feed-Thru.
Maximum Interrupting Capacity	10,000A.
Operating Temperature	-35°C to 66°C or -30°F to 150°F.
Maximum Humidity	95%.
Listings and Standards	Meets UL498 for receptacles, UL943 Class A for GFCIs UL File E41978 CSA Certified.
Codes	Meets all NEC® and CEC requirements. NEMA WD-6 ANSI 73.

NEC® is a registered trademark of the National Fire Protection Association (NFPA).