

# Straight Blade Devices

## Accessories

For 4 Wire 30, 50 and 60 Ampere, 125/250 Volts, 3Ø 250 and 3ØY 120/208 Volts AC



SS701



### Wallplates, 2-Gang

#### Description

Brass .04 in. (1.0), brushed, smooth.  
Stainless steel 302/304, .035 in. (0.9),  
smooth horizontal brushed finish.

Single Receptacle Plate  
2.48 in. (63.0) Dia.  
Catalog Number

**SB701**

**SS701**



HBL7777A



**IP44**  
SUITABILITY

### Weatherproof Lift Covers

#### Description

RTP, gray, lift cover plate. Will fit FS/FD boxes having plate mounting  
hole 3.25 in. x 3.75 in. (82.5 x 95.2), centers. Only for use with  
receptacles on pages A-40 to A-43 with "A" suffix.

Same as above except yellow.

*Note: RTP is an abbreviation for reinforced thermoplastic polyester.*

Catalog Number

**HBL7777A**

**HBL77CM77A**



HLD2

### PLUGOUT® Device

#### Description

Electrical plug lockout device for 30, 50 and 60A devices.

*Note: See section BB for additional information on lockout devices.*

Catalog Number

**HLD2**

Dimensions in Inches (mm)