







15 and 20 Ampere, 125 Volts



Dimensions in Inches (mm)

Commercial Specification Grade Receptacles



Duplex

Smooth polycarbonate face, duplex, back and side wired.

Color

Catalog Number

Tamper-Resistant, smooth polycarbonate face, duplex, back and side wired.	Black	BR15BLK	BR20BLK
	Blue	BR15BL	BR20BL
	Brown	BR15	BR20
	Gray	BR15GRY	BR20GRY
	Green	BR15GN	BR20GN
	Ivory	BR15I	BR20I
	Light Almond	BR15LA	BR20LA
	Red	BR15R	BR20R
	White	BR15WHI	BR20WHI
	Tamper-Resistant, smooth polycarbonate face, duplex, back and side wired.	Black	BR15BLKTR
Blue		BR15BLTR	BR20BLTR
Brown		BR15TR	BR20TR
Gray		BR15GRYTR	BR20GRYTR
Green		BR15GNTR	BR20GNTR
Ivory		BR15ITR	BR20ITR
Light Almond		BR15LATR	BR20LATR
Red		BR15RTR	BR20RTR
White		BR15WHITR	BR20WHITR
Weather Resistant, smooth polycarbonate face, duplex, back and side wired.		Black	BR15BLKW
	Brown	BR15W	BR20W
	Gray	BR15GRYW	BR20GRYW
	Ivory	BR15IW	BR20IW
	Light Almond	BR15LAW	BR20LAW
	White	BR15WHIW	BR20WHIW
Weather and Tamper-Resistant, smooth polycarbonate face, duplex, back and side wired.	Black	BR15BLKWTR	BR20BLKWTR
	Brown	BR15WRTR	BR20WRTR
	Gray	BR15GRYWTR	BR20GRYWTR
	Ivory	BR15IWRTR	BR20IWRTR
	Light Almond	BR15LAWTR	BR20LAWTR
	White	BR15WHIWRTR	BR20WHIWRTR
Isolated ground ^A , smooth nylon face, duplex, side wired only.	Gray	IG15CRGRY	IG20CRGRY
	Ivory	IG15CRI	IG20CRI
	Light Almond	IG15CRLA	IG20CRLA
	Orange	IG15CR	IG20CR
	White	IG15CRWHI	IG20CRWHI
Isolated ground ^A , Style Line [®] decorator*, smooth nylon face, duplex, back and side wired.	Gray	IG15DRGRY	IG20DRGRY
	Ivory	IG15DRI	IG20DRI
	Light Almond	IG15DRLA	IG20DRLA
	Orange	IG15DR	IG20DR
	White	-	IG20DRWHI

Note: ^ASee section N for additional information on isolated ground devices.
 See page A-47 for accessories.
 See page Tech-10 for Tamper and Weather Resistant descriptions.
 See section O for wallplates.