



# Compression Splice Conventional (Two Die) Full Tension

by FARGO  
Catalog ID: TJA2209SSAC

Compression Splice, Conventional 2-Die, Full Tension , for ACSS 556.5  
kcmil 26/7



\* Representative image

## Product Details

### General

Aluminum Die	24AH
Compression Method	Conventional (2 die system)
Inhibitor Loaded	No
Material	Aluminum; Steel
Press Minimum	60 to
Tension Range	0 lb
UPC	096359482611

### Dimensions

Adjustment Step	0 in
Assembly Rating (Ultimate)	0 lb
Diameter - Outside	0.927 in
Insulator / Conductor Hole Spacing	0 in
Length Before Compression	30.1 in
Weight	3.773 lb

### Electrical Ratings

Voltage Application	Standard
---------------------	----------

### Conductor Related

Conductor Compatibility	ACSS-Dove-556.5-26/7
Conductor Diameter (Main) - Maximum	0 in
Conductor Diameter (Main) - Minimum	0 in
Conductor Type	ACSS
Messenger Diameter - Maximum	0 in
Messenger Diameter - Minimum	0 in

### Certifications and Compliance

UL Listed	No
-----------	----

### Logistics

Pallet Quantity	180 EA
-----------------	--------

**For further technical assistance, please contact us**

**Domestic Customer Service**

Hubbell Power Systems

210 N. Allen Centralia, MO 65240 USA

Phone: (573) 682-5521

Fax: (573) 682-8475

Email: [hpscsc@hubbell.com](mailto:hpscsc@hubbell.com)

**International Customer Service**

Phone: +1-573-682-5521

Fax: +1-573-682-8516

Email: [hpsintlcs@hubbell.com](mailto:hpsintlcs@hubbell.com)