



GE
Lighting

72550 - 75A/RS/STG-TP6

GE saf-t-gard® 75/67 watt A21 1-pack

- 130/120 volts
- 2800K soft white light appearance
- A21 shape with medium base for use in rough service applications
- GE saf-t-gard® bulbs feature a protective Teflon® coating that helps contain glass fragments if broken. Designed with heavy-duty, all-weather construction, these bulbs protect against shattering, rain breakage and splatter from oil and lubricants. GE saf-t-gard® bulbs are perfect for home use in kitchens, basements garages, workshops and enclosed exterior fixtures
- Estimated yearly energy costs \$9.03/\$8.07 based on 3 hours per day \$0.11 per kWh
- Lasts 1.8/4.9 years based on 3 hours per day usage
- Provides 560/740 lumens



GENERAL CHARACTERISTICS

Lamp Type	Incandescent - A-line
Bulb	A21
Base	Med Screw (E26)
Filament	C-7A
Bulb Finish	Inside frost
Rated Life	2000.0 hrs
Bulb Material	Soft glass
Additional Info	Rough Service, Saf-T-Gard®

Primary Application	Standard
---------------------	----------

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	740.0 /560.0
Color Temperature	2800.0 K

ELECTRICAL CHARACTERISTICS

Wattage	75.0
Voltage	130.0

DIMENSIONS

Maximum Overall Length (MOL)	4.1300 in(104.9 mm)
Bulb Diameter (DIA)	2.625 in(66.7 mm)
Light Center Length (LCL)	2.910 in(73.9 mm)

PRODUCT INFORMATION

Product Code	72550
Description	75A/RS/STG-TP6
Standard Package	00-Case
Standard Package GTIN	10043168725504
Standard Package Quantity	6
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	6
UPC	043168725507