



71598 - 55PAR/HIR+/FL25

GE HIR™ PLUS PAR38

Up to 60% longer life -4000 hours









CAUTIONS & WARNINGS

Caution

- Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.
- Risk of Burn
- Allow lamp to cool before handling.
- · Lamp may shatter and cause injury if broken
- Do not use lamp if outer glass is scratched or broken.
- Risk of Burn
- Allow lamp to cool before handling.

Warning

- Unexpected lamp rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Fire
- Keep combustible materials away from lamp.
- Risk of Electric Shock
- Turn power off before inspection, installation or removal.
- Unexpected lamp rupture may cause injury, fire, or property damage
- Do not use lamp if outer glass is scratched or broken.

GENERAL CHARACTERISTICS

Lamp Type Bulb Base Filament Rated Life Life in Years Primary Application Halogen - PAR PAR38 Medium Skirt (E26/50x39) CC-8 4200.0 hrs 3.8 Indoor and outdoor Floodlight

PHOTOMETRIC CHARACTERISTICS

Initial Lumens1120.0Center Beam Candlepower4100.0(CBCP)2750.0 KColor Temperature2750.0 KBeam Spread25.0 °Nominal Initial Lumens per Watt20

ELECTRICAL CHARACTERISTICS

Wattage55.0Voltage120.0Estimated Energy Cost per6.62YearYear

DIMENSIONS

Maximum Overall Length (MOL) Bulb Diameter (DIA) 5.3130 in(135.0 mm)

4.750 in(120.6 mm)

PRODUCT INFORMATION

Product Code Description Standard Package Standard Package GTIN Standard Package Quantity Sales Unit No Of Items Per Sales Unit No Of Items Per Standard Package UPC

043168715980