

# Eaton XTCEXFAC11

Catalog Number: XTCEXFAC11

Eaton motor control auxiliary contact, Two-pole, Screw terminals, 1NO-1NC contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton motor control auxiliary contact	XTCEXFAC11
<b>EAN</b>	<b>Product Length/Depth</b>
4015082764210	1.5 in
<b>Product Height</b>	<b>Product Width</b>
1.5 in	2 in
<b>Product Weight</b>	<b>Compliances</b>
0.08 lb	ATEX Compliant
	CE Marked
	CCC Marked
<b>Certifications</b>	<b>Catalog Notes</b>
IEC 60947	Interlocked opposing contacts, to IEC/EN
EN 60947	60947-5-1 Annex L (positively driven),
UL Listed	within the auxiliary contact modules (not
CSA Certified	NOE and NCL contacts) and between
	the auxiliary contacts and built-in
	contacts of the XTRE control relays.

## defaultTaxonomyAttributeLabel

### Number Of Poles

Two-pole

### Type

Contactory Accessory - Auxiliary Contact

### Used with

XTRE control relays

### Terminals

Screw

### Contact configuration

1 NO-1 NC

### Mounting method

Front

### Rated operational current

6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V

### Conventional thermal current

16A

### Quantity

5

## Resources

### Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

### Specifications and datasheets

[Global Data Sheet - XTCEXFAC11](#)

[Eaton Specification Sheet - XTCEXFAC11](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)