

Eaton XTCEXFAC40

Catalog Number: XTCEXFAC40

Contactor Accessory - Auxiliary Contact, Four-pole, Screw terminals, 4NO contact configuration, 16A conventional thermal rating, 6A at 220/230/240V, 3A at 380/400/415V, 1.5A at 500V rated operational voltage, Front mounting,

General specifications



Photo is representative

Product Name	Catalog Number
Eaton motor control auxiliary contact	XTCEXFAC40
EAN	Product Length/Depth
4015082764289	1.5 in
Product Height	Product Width
1.5 in	2.5 in
Product Weight	Warranty
0.1 lb	Not Applicable
Compliances	Certifications
ATEX Compliant	IEC 60947
CE Marked	EN 60947
CCC Marked	UL Listed
	CSA Certified

Catalog Notes

Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.

defaultTaxonomyAttributeLabel

Number Of Poles

Four-pole

Type

Contactory Accessory - Auxiliary Contact

Used with

XTRE control relays

Terminals

Screw

Contact configuration

4 NO

Mounting method

Front

Rated operational current

6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V

Conventional thermal current

16A

Quantity

5

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Specifications and datasheets

[Global Data Sheet - XTCEXFAC40](#)

[Eaton Specification Sheet - XTCEXFAC40](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)