

Eaton XTOBP24CC1

Catalog Number: XTOBP24CC1

Eaton XT IEC bimetallic overload relay, 0.16-0.24A overload range, 45 mm Frame size, 1NO-1NC contact configuration, Direct mounting, used with 18-32A contactor, 10A trip type



Photo is representative

General specifications

Product Name

Eaton XT IEC bimetallic overload relay

Catalog Number

XTOBP24CC1

EAN

4015082784430

Product Length/Depth

3.27 in

Product Height

1.89 in

Product Width

1.77 in

Product Weight

0.3 lb

Compliances

CE Marked

RoHS Compliant

ATEX Compliant

Certifications

UL Listed

CSA Certified

IEC 60947

EN 60947

Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.



Powering Business Worldwide

defaultTaxonomyAttributeLabel

Overload range

0.16-0.24 A

Frame size

45 mm

Mounting

Direct

Resources

Brochures

[C440 Electronic Overload Relay](#)

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTOB_CC1 3D Inventor](#)

[XTOB_CC1 3D Model Xchange](#)

[XTOB_CC1 2D Drawing Xchange](#)

[XTOB_CC1 2D PDF](#)

[XTOB_CC1 AutoCAD 2D Footprint \(mm\)](#)

[XTOB_CC1 AutoCAD 2D Footprint](#)

Multimedia

[Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained](#)

Specifications and datasheets

[Global Data Sheet - XTOBP24CC1](#)

[Eaton Specification Sheet - XTOBP24CC1](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)