

Eaton XTOBP40BC1

Catalog Number: XTOBP40BC1

Eaton XT IEC bimetallic overload relay, 0.24-0.4A overload range, 45 mm Frame size, 1NO-1NC contact configuration, Direct to contactor mounting, used with 7-15A contactor, 10A trip type

General specifications



Product Name

Eaton XT IEC bimetallic overload relay

Catalog Number

XTOBP40BC1

EAN

4015082784331

Product Length/Depth

3.27 in

Product Height

1.89 in

Product Width

1.77 in

Product Weight

0.3 lb

Compliances

RoHS Compliant
ATEX Compliant
CE Marked

Certifications

UL Listed
CSA Certified
IEC 60947
EN 60947

Catalog Notes

Observe the maximum permissible fuse of the contactor with direct device mounting. Suitable for protection of EEx e-motors. EC prototype test certificate available upon request.

defaultTaxonomyAttributeLabel

Overload range

0.24-0.4 A

Frame size

45 mm

Mounting

Direct

Resources

Brochures

[C440 Electronic Overload Relay](#)

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTOB_BC1 2D PDF](#)

[XTOB_BC1 2D Drawing Xchange](#)

[XTOB_BC1 AutoCAD 2D Footprint \(mm\)](#)

[XTOB_BC1 AutoCAD 2D Footprint](#)

[XTOB_BC1 3D Model Xchange](#)

[XTOB_BC1 3D Inventor](#)

Multimedia

[Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained](#)

Specifications and datasheets

[Global Data Sheet - XTOBP40BC1](#)

[Eaton Specification Sheet - XTOBP40BC1](#)



Eaton Corporation plc

Eaton House

30 Pembroke Road

Dublin 4, Ireland

Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)