



Energy Advantage IR PAR38

Energy Advantage IR 100PAR38/IRC+/SP10 120V 12PK

Due to the heat that radiates from the bulb, a minimum distance of 4 ft is required between bulb and combustible materials or objects susceptible to drying or fading

Product data

General Information	
Cap-Base	E26/50X39 [Skirted Medium Screw (PAR Lamps)]
Operating Position	Universal [Universal]
Main Application	Outdoor (OD)
Gas Filling	GAS

Light Technical	
Beam Angle (Nom)	10 °
Initial lumen (Nom)	2200 lm
Luminous Intensity (Nom)	26400 cd
Beam Description	Spot
Correlated Color Temperature (Nom)	2900 K
Color Rendering Index (Nom)	100


Operating and Electrical	
Power (Rated) (Nom)	100 W
Voltage (Nom)	120 V

Mechanical and Housing	
Bulb Finish	Clear (CL)
Cap-Base Information	Brass [Brass Cap]
Bulb Material	Hard Glass
Reflector Finish	Aluminized
Filament Shape	CC-8 [Axial]

Product Data	
Order product name	Energy Advantage IR 100PAR38/IRC+/SP10 120V 12PK
EAN/UPC - Product	046677138769
Order code	138768
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	924757117403
Net Weight (Piece)	370.000 g

Energy Advantage IR PAR38

Dimensional drawing



Product	D	C (max)
Energy Advantage IR 100PAR38/IRC+/SP10 120V 12PK	4.75 in	5.313 in

PAR38 IRC 100W E26/50x39 120V Spot 10D

