



# Energy Advantage IR PAR30

## Energy Advantage IR 50PAR30S/IRC+/FL25 120V 15PK

Due to the heat that radiates from the bulb, a minimum distance of 2 ft is required between bulb and combustible materials or objects susceptible to drying or fading

### Product data

General Information	
Cap-Base	E26 [ Single Contact Medium Screw]
Operating Position	Universal [ Universal]
Main Application	Outdoor (OD)
Gas Filling	GAS
Life with 3 Hour Per Day Use	3.8 a
Light Technical	
Beam Angle (Nom)	25 °
Initial lumen (Nom)	900 lm
Luminous Intensity (Nom)	3850 cd
Beam Description	Flood [ Flood]
Correlated Color Temperature (Nom)	2740 K
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	50 W
Voltage (Nom)	120 V
Mechanical and Housing	
Bulb Finish	Clear (CL)

Cap-Base Information	Brass [ Brass Cap]
Bulb Material	Hard Glass
Reflector Finish	Aluminized
Filament Shape	CC-8 [ Axial]

### Approval and Application

Estimated Energy Cost Per Year	6.02 \$
--------------------------------	---------


### Product Data

Order product name	Energy Advantage IR 50PAR30S/IRC+/FL25 120V 15PK
EAN/UPC - Product	046677145002
Order code	145003
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	15
Material Nr. (12NC)	924757120402
Net Weight (Piece)	190.000 g

# Energy Advantage IR PAR30

## Dimensional drawing

Product	D	C (max)
Energy Advantage IR 50PAR30S/IRC+/FL25 120V 15PK	3.75 in	3.625 in



PAR30S IRC 50W E26/Brass 120V Flood 25D

