PHILIPS Lighting



Reflector Flood

65BR30/FL55 CDA 130V

Philips Family of Specialty Incandescents provide the perfect light for dramatic accents and display lighting as well as general lighting in a variety of applications. These flood lamps produce homogeneous beams of high intensity for general illumination.

Product data

General Information	
Cap-Base	E26 [Single Contact Medium Screw]
Operating Position	Universal [Universal]
Main Application	Indoor Reflector
Gas Filling	GAS
Life with 3 Hour Per Day Use	1.8 a
Footnote Incandescent 1	Consider the compact fluorescent lamps for energy
	savings.
Footnote Incandescent 2	Do not allow hot bulb to come in contact with liquid or
	metal parts of the fixture, as glass may shatter. Do not
	use outdoors. Do not operate in close proximity to
	flammable materials or those adversely affected by
	heat or drying. Operate only in heat resistant sockets.
	(87)
Light Technical	
Beam Angle (Nom)	55 °
Initial lumen (Nom)	605 lm
Beam Description	Flood [Flood]
Luminous Flux Lamp @ 120V	450 lm
Correlated Color Temperature (Nom)	2680 K
Operating and Electrical	
	65 W


Lamp Wattage Rated@120V	55 W
Voltage (Nom)	130 V
Mechanical and Housing	
Bulb Finish	Frosted (FR)
Cap-Base Information	Aluminium [Aluminium Cap]
Filament Shape	CC6 [Straight]
Approval and Application	
Estimated Energy Cost Per Year at 120V	6.67 \$
Estimated Energy Cost Per Year	7.83 \$
Product Data	
Order product name	65BR30/FL55 CDA 130V
EAN/UPC - Product	046677225209
Order code	248849
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	920681036112
Net Weight (Piece)	0.001 kg

Reflector Flood

Dimensional drawing

Product

65BR30/FL55 CDA 130V



65W E26 130V BR30 FL FR



© 2016 Philips Lighting Holding B.V. All rights reserved. Philips Lighting reserves the right to make changes in specifications and/or to discontinue any product at any timewithout notice or obligation and will not be liable for any consequences resulting from the use of this publication.

www.lighting.philips.com 2016, October 11 - data subject to change