## Rittal - The System.

Faster – better – everywhere.

## Compact enclosures AE − AE 1350.500

Date: May 24, 2018



NCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

## Compact enclosures AE - AE 1350.500

created: 24.05.2018 build on www.rittal.com/us-en



Prod	uct d	escri	ption
	act a	<b>000:</b> :	P (1 V 1 1

Material: Housing: Carbon steel

Door: Carbon steel, all-round foamed-in PU seal

**Surface finish:** Housing and door: Dipcoat primed, powder-coated on the outside, textured paint

Mounting plate: Zinc-plated

Color: RAL 7035

Protection category IP to IEC 60 529:

IP 66

**Protection category** 

NEMA:

NEMA 4

IK code:

**IK08** 

----

Supply includes:

Housing with hinged door(s), of all-round solid construction

Flange (gland) plate(s) in enclosure base

Mounting plate

Lock: 3 mm double-bit

Base material:

Carbon steel

## **Product features**

Dimensions: Height: 500 mm (20 ")

Width: 500 mm (20 ") Depth: 300 mm (12 ")

Material thickness:: Housing: 1.5 mm (0.06 ")

Door: 1.75 mm (0.07 ")

© Rittal 2018

Mounting plate: 2.5 mm (0.1 ")

Mounting plate:	Height: 470 mm (19 ") Width: 449 mm (18 ")	
Number of doors:	1	
Door catch on right, may be swapped to the left:	yes	
Lock version:	Cam	
No. of locks:	2	
Lock Insert:	3 mm double-bit	
Flange plate, size:	4	
Flange plate, qty:	1	
Packaging unit:	1 pc(s).	
Weight/packaging unit:	19.6 kg	
EAN:	4028177252486	
Customs tariff number:	94032080	
ETIM 6.0:	EC000261	
ETIM 5.0:	EC000261	
eCl@ss 8.0/8.1:	27180101	
eCl@ss 7.0/7.1:	27180101	
eCl@ss 6.0/6.1:	27180101	
e Cl@ss 5.1/5.1.4:	27180102	
Product description (long):	AE Compact enclosure, WHD: 500x500x300 mm, Sheet steel, with mounting plate, single-door, with two cam locks	
Approvals		
Approvals:	Bureau Veritas CSA DNV-GL	
•		

© Rittal 2018

Lloyds Register of Shipping RRR

Russian Maritime Register of Shipping

TÜV UL + C-UL

Certificates: EAC

IK-Code

Protection category

**Declarations:** Declaration of conformity

© Rittal 2018