## Rittal - The System.

Faster – better – everywhere.

## ■ Wallmounted enclosure Stainless steel – WM 8017.600

Date: May 24, 2018



ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

## Wallmounted enclosure Stainless steel – WM 8017.600 - WM242408N4

created: 24.05.2018 build on www.rittal.com/us-en



Prod	luct	aah	crin	tion
riuu	uci	ues	CHID	เมษา

Material: Door: Stainless steel, all-round foamed-in PU seal

Housing and door: Stainless steel 1.4301 (AISI 304)

Mounting plate: Carbon steel, zinc-plated

Surface finish: Brushed

Protection category IP to IEC 60 529:

IP 66

**Protection category** 

NEMA:

**NEMA 4X** 

Supply includes:

Housing with door(s) Left hand hinge Mounting plate

Wall mounting blind-nuts

## **Product features**

**Dimensions:** Height: 600 mm (24 ")

Width: 600 mm (24 ") Depth: 210 mm (8.3 ")

Material thickness:: Housing: 1.5 mm (0.06 ")

Door: 2 mm (0.08 ")

Mounting plate: 2.5 mm (0.1 ")

Mounting plate: Height: 570 mm (22 ")

Width: 549 mm (22 ")

© Rittal 2018

Lock version:	Quarter turn
Packaging unit:	1 pc(s).
Weight/packaging unit:	26 kg (57.3 lb.)
EAN:	83177
Approvals	
Approvals:	UL + C-UL

© Rittal 2018