

T150M9X2



Article Number: 111-15619

Heavy Duty Cable Tie, 21" Long, 175 lb Tensile Strength, PA66, Natural, 25/pkg



Base Data

Local Order Number T150M9X2

Type T150M

Color Natural (NA)

- Features and Benefits**
- Heavy duty design to offer higher tensile strength.
 - Head design provides high tensile strength with very low insertion force.

Product Description HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Heavy Duty Cable Tie, 21" Long, 175 lb Tensile Strength, PA66, Natural, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 175.0 lbs

Minimum Tensile Strength (N) 780.0 N

Length L (imperial) 21.0 "

Length L (metric) 530.0 mm

Width W (imperial) 0.35 "

Width W (metric) 8.9 mm

Bundle Diameter min (imperial) 0.32 "

Bundle Diameter min (metric) 8.0 mm

Bundle Diameter max (imperial) 5.9 "

Bundle Diameter max (metric) 150.0 mm

Thickness T (imperial) 0.075 "

Cable Tie Head Height (Metric) 9.5 mm

Cable Tie Head Length (metric) 14 mm

Cable Tie Head Width (metric) 14 mm

Cable Tie Head Length (imperial) 0.55 "

Cable Tie Head Width (imperial) 0.55 "

Thickness T (Metric) 1.9 mm

Logistics and Packaging

| | |
|-------------------------|--------|
| Quantity per | bag |
| Package Quantity | 25 |
| Carton Quantity | 1000 |
| Weight (Metric) | 8.4 kg |

Material and Specifications

| | |
|--------------------------------------|--------------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| CSA Certified | No |
| Flammability | UL94 V2 |
| Halogenfree | Yes |
| Operating Temperature | -40 °F to +185 °F (-40 °C to +85 °C) |
| ROHS Conformity | Yes |
| Certification / Specification | UL ZODZ2.E64139 |
| UL Listed (US and Canada) | No |
| UL Recognized (US and Canada) | Yes |