



## 1/2 in. 150 Degree Rigid/IMC Grounding Bushing, Feed-Through- Lug, Insulated

By Raco  
Catalog # [1222](#)

1/2 in. 150 Degree Rigid/IMC Grounding Bushing, Feed-Through-Lug, Insulated



\*Representative Image

### Features

- Malleable iron construction ensures mechanical protection
- Zinc-electroplated for added corrosion protection
- Insuliner rated for 150° C
- Grounding Wire Capacity - #14 Sol. - #4 Str.
- UL and CSA Listed
- Available in trade sizes of 1/2 in. through 4 in.

### General

|                   |                      |
|-------------------|----------------------|
| Conduit Type      | Rigid/IMC            |
| Connector Type    | Grounding            |
| EU RoHS Indicator | Contact Manufacturer |
| Fitting Type      | Bushings             |
| Insulation Type   | Insulated            |
| Material          | Malleable Iron       |
| UPC               | 050169012222         |

### Dimensions

|            |                                |
|------------|--------------------------------|
| Dimensions | 0.578 in x 1.156 in x 1.656 in |
| Height     | 1.656 in                       |
| Length     | 0.578 in                       |
| Trade Size | 1/2 in                         |
| Weight     | 0.073 lb                       |
| Width      | 1.156 in                       |

### Electrical Ratings

|                                    |         |
|------------------------------------|---------|
| Grounding Wire Capacity<br>Maximum | #4 STR  |
| Grounding Wire Capacity<br>Minimum | #14 SOL |

### Certifications And Compliance

|                  |                                                                                     |
|------------------|-------------------------------------------------------------------------------------|
| Certified Listed | <ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul> |
|------------------|-------------------------------------------------------------------------------------|

|                      |         |
|----------------------|---------|
| Industry Standard(s) | UL 514B |
|----------------------|---------|

### Logistics

|                       |       |
|-----------------------|-------|
| Carton Quantity       | 100   |
| Minimum Pack Quantity | 100   |
| Pallet Quantity       | 32000 |

### Product Assets

[Catalogs - RACO / TayMac / Bell Full Catalog](#)  
[Certifications - UL COC-E195975-1](#)  
[Product Logo - Conduit](#)  
[SDS - HCC\\_SDS](#)  
[Terms and Conditions - HCC Terms & Conditions](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
RACO-1222-SPEC-EN | REV 5/2024