

## MB3A10C2

**Article Number:** 151-28718

**Adhesive Bases, .14" Max tie width, .75" Length/Width, .12" Hole Dia., PA66, White, 100/pkg**



### Base Data

**Local Order Number** MB3A10C2

**Type** MB3A

**Color** White (WH)

- Features and Benefits**
- For use with 18 and 30 pound cable ties to provide stability when securing bundles.
  - Secures with acrylic based adhesive backing for heavy bonding applications
  - Can also be secured using two or four screws; providing multiple options.
  - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Fixation Method (FF)** Screw Mounting and Adhesive

**Short Description** Adhesive Bases, .14" Max tie width, .75" Length/Width, .12" Hole Dia., PA66, White, 100/pkg

### Product Dimensions

**Length L (imperial)** 0.75 "

**Length L (metric)** 19.0 mm

**Width W (imperial)** 0.75 "

**Width W (metric)** 19.0 mm

**Cable Tie Width Max (imperial)** 0.14 "

**Cable Tie Width max. (metric)** 3.6 mm

**Height H (imperial)** 0.18 "

**Height H (metric)** 4.6 mm

**Mounting Hole Diameter D (imperial)** 0.12 "

**Mounting Hole Diameter D (metric)** 3.0 mm

**Mounting Hole Centers (imperial)** 0.52 "

**Thickness of Adhesive TA (imperial)** 0.031 "

**Mounting Hole Centers (metric)** 13.2 mm

**Thickness of Adhesive TA (metric)** 0.8 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 100

**Carton Quantity** 10000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

|                                       |   |
|---------------------------------------|---|
| <b>Material Shortcut</b>              | PA66  |
| <b>Adhesive</b>                       | Synthetic rubber with base of polyethylene foam |
| <b>Shortcut Adhesive</b>              | Synthetic rubber                                |
| <b>Adhesive Operating Temperature</b> | -4 °F to +122 °F (-20°C to +50°C)               |
| <b>CSA Certified</b>                  | No  |
| <b>Flammability</b>                   | UL94 V2 (excluding adhesive)                    |
| <b>Operating Temperature</b>          | -40 °F to +185 °F (-40 °C to +85 °C)            |
| <b>ROHS Conformity</b>                | Yes   |
| <b>UL Listed (US and Canada)</b>      | No  |
| <b>UL Recognized (US and Canada)</b>  | Yes   |