

# Rittal – The System.

Faster – better – everywhere.

## **Wallmounted enclosure – WM 1350.250**

Date : May 24, 2018

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Wallmounted enclosure – WM 1350.250 - WM202012NC

created: 24.05.2018 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert

## Product features

Dimensions:	Height: 500 mm (20 ") Width: 500 mm (20 ") Depth: 300 mm (12 ")
Material thickness::	Housing: 1.5 mm (0.06 ") Door: 1.5 mm (0.06 ") Mounting plate: 2.5 mm (0.1 ")
Mounting plate:	Height: 470 mm (19 ") Width: 449 mm (18 ")

<b>Packaging unit:</b>	1 pc(s).
<b>Weight/packaging unit:</b>	20 kg (44.1 lb.)
<b>EAN:</b>	83114
<b>Approvals</b>	
<b>Approvals:</b>	UL