

Specification Sheet

Part Number: 2NFP0C



Sheathing allows flexible routing and lead-out of cables.

The inner edges are beveled preventing damage to cables.

Sheathing is reusable and resistant to most chemicals.

Spiralwrap is U.L. Recognized.

|                     |                                                                                                                                                                          |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article Number      | 161-05036                                                                                                                                                                |
| Type                | 2NFP                                                                                                                                                                     |
| Color               | Black (BK)                                                                                                                                                               |
| Quantity Per        | pack                                                                                                                                                                     |
| Product Description | HellermannTyton’s Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize. |
| Short Description   | Spiralwrap Protective Sheathing, 0.25" Diameter, PE, Black, 100 ft/roll                                                                                                  |
| Global Part Name    | 2NFP-PE-BK                                                                                                                                                               |

|                                |                   |
|--------------------------------|-------------------|
| Length L (Imperial)            | 100.0             |
| Length L (Metric)              | 30.48             |
| Variant                        | Spiral Binding    |
| Bundle Diameter Min (Imperial) | 0.19              |
| Bundle Diameter Min (Metric)   | 4.75              |
| Bundle Diameter Max (Imperial) | 2                 |
| Bundle Diameter Max (Metric)   | 50.8              |
| Diameter D (Imperial)          | 0.25              |
| Diameter D (Metric)            | 6.35              |
| Nominal Diameter (Imperial)    | 0.25              |
| Nominal Diameter (Metric)      | 6.35              |
| Wall Thickness WT (Imperial)   | 0.045             |
| Wall Thickness WT (Metric)     | 1.14              |
| Material                       | Polyethylene (PE) |
| Material Shortcut              | PE                |

|                              |                                  |
|------------------------------|----------------------------------|
| Halogen Free                 | No                               |
| UV Resistant (Yes/No)        | Yes                              |
| Operating Temperature        | -76°F to +190°F (-60°C to +88°C) |
| Reach Compliant (Article 33) | Yes                              |
| ROHS Compliant               | Yes                              |
| UL Recognized (US)           | Yes                              |
| Package Quantity (Imperial)  | 100                              |
| Package Quantity (Metric)    | 30.48                            |
| Customs Number               | 3926909988                       |

7930 N. Faulkner Road, Milwaukee, WI 53224  
 Phone: (800) 537-1512 | Email: corp@htamericas.com