

CATALOG NUMBER: DESCRIPTION: APPROVALS:	See table below SJTW replacement power supply cords UL / CUL Listed				
CONSTRUCTION PARAMETERS:					
	14/3	14/3			
Condu		41/30 Bare Copper			
Conduct	0.074 in				
Insulated conduct		0.136 in			
Insul	PVC	PVC			
Ins	Black W	Black White Green			
Overall cab		0.370 in			
Ji	PVC, bla	PVC, black			
Note: Plug style may vary					
Attachment plug configuration: NEMA 5-15P					
	PVC, bla	PVC, black			
Open end	2.5" RO	2.5" ROJ, 0.5" conductor strip & retain			
ELECTRICAL PROPERTIES:					
Cable temp	-40 to +6	-40 to +60 °C			
Nominal ope	125 VAC	125 VAC			
Maximum operating current: 1			15 A		
CATALOG NUMBERS:					
Catalog number	Length	Case qty	UPC		
97168808	6 ft	25	0 29892 09716 5		
97198808	9 ft	25	0 29892 09719 6	]	

This product complies with European Directive 2011/65/EU (RoHS-2,

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part.

We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is the proprietary intellectual property of Southwire Company LLC. Any information contained herein shall not be disclosed to any party without the written consent of Southwire Company LLC.