



# SB-1H



VIDEO

## Product Description

Single gang adjustable electrical box for use with nonmetallic sheathed cable

**Brand:** SLIDERBOX®  
**Catalog #:** SB-1H

**Height:** 2-5/16 in.  
**Width:** 3-3/4 in.  
**Depth:** 3-9/16 in.  
**Volume:** 23 cu. in.

**Type of Installation:** Old or New Work  
**Wall Box**  
**Number of Gangs:** 1

**Carton Quantity:** 12  
**Carton Weight:** 4 lb.

**UPC:** 085339945031  
**UNSPSC:** 39121308

**Patents:**  
U.S. Patent No. 7,855,338  
**Country of Origin:** United States of America

## FEATURES

Horizontal mount design with molded-in splined device holes, adjustable slider plate for additional wall substrate thickness, rectangular exterior for easy cut-in, leveling ribs, offset gauge marks

## APPLICATION

New and old work residential construction 2 HR fire resistive walls and ceilings

## STANDARDS

ANSI / UL 514C: File No. E30594



## FIRE CLASSIFICATION

### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)  
*Note: Products must also be certified to: ANSI / UL 514C*

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes must be 4-½ feet from one another

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

## COLOR

Beige/tan

## ADDITIONAL MATERIALS

Carbon steel fasteners

## MATERIAL

Polyvinyl Chloride

Polycarbonate adjustable mounting plate

## MOUNTING

Horizontal mount design with internal screws with adjustable slider plate for substrates 1/2" to 1 3/8"