Eaton M2S03FC2

Catalog Number: M2S03FC2

Eaton Cooper Power series M-Force three-phase switch, 27.0 kV, 900A (new), 150 kV, 2.25" BC, Hookstick operated (no control rod), Cycloaliphatic epoxy, Fiberglass - 2 point lift, Vertical riser (G095 spacing), No handle

General specifications

Product Name	Catalog Number
Eaton Cooper Power series M-Force	M2S03FC2
three-phase switch	UPC 786689709204
Product Length/Depth	Product Height
128 in	25.5 in
Product Width	Product Weight
25 in	0.001 lb
Compliances Not Applicable	Certifications IEEE Std 1247 IEEE Std C37.34



Description

Control rod and mechanism

Hookstick operated (no control rod)

Crossarm material Fiberglass - two point lift

Insulator bolt pattern 2.25" BC

Material type Cycloaliphatic epoxy

Switch type M-Force switch

Electrical Ratings

Amperage Rating 900A Basic impulse level 150 kV Number of phases

Three-phase

Voltage rating

27.0 kV

M-Force Switch

Mounting configuration (M-force only) Vertical riser (G095 spacing)

Operating handle configuration (M-force only) No handle

Resources

Brochures M-Force Three-Phase Switch Catalog

Specifications and datasheets

Eaton Specification Sheet - M2S03FC2



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2023 Eaton. All Right Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2023 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia