


S025030S2010




Product Specifications

Typical System Voltage	69kV / 115kV
Strength Class	25 kip, 5/8" (16 mm)
Top/Ground End Fitting	Y-Clevis
Bottom/Line End Fitting	ANSI Ball
Section Length	41.94 IN (1065 MM)
Leakage Distance	77 IN (1956 MM)
Corona Ring	None
Polymer Length	30.14 IN (766 MM)
System Voltage (kV)	115kV
Working Load	12,500 lbs
Dry Arc Distance	30.2 IN (766 MM)
Number of Sheds	28
Shed Style	Uniform
Shed Diameter	2.9 IN
Rod Diameter	5/8 IN (16 MM)
Thickness of housing over Rod	> 3MM
End Fitting Class	ANSI
End Fitting Material	Ductile Iron
SML	25,000 lbs
RTL	12,500 lbs
ANSI 60Hz Dry FO	315 kV
Housing Material	SILICONE RUBBER
ANSI 60Hz Wet FO	305 kV
ANSI 60Hz Wet Withstand	190 kV
IEC lightning Impulse Withstand - Positive	525 kV
ANSI Critical Impulse FO - Positive	445 kV
IEC lightning Impulse Withstand - Negative	510 kV
ANSI Critical Impulse FO - Negative	430 kV

Compressed Product Number

S025030S2010



[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.