## Product data sheet Characteristics

# XX918A3C2M12

ultrasonic sensor cylindrical M18 - Sn 0.5 m - 4..20 mA - M12 connector

Product availability: Stock - Normally stocked in distribution facility



#### Main

IVIAIII		
Range of product	OsiSense XX	
Sensor type	Ultrasonic sensor	
Series name	General purpose	
Sensor name	XX9	
Sensor design	Cylindrical M18	
Detection system	Diffuse	
[Sn] nominal sensing distance	1.64 ft (0.5 m) adjustable with remote teach push-button	
Material	Plastic	
Type of output signal	Analogue	
Wiring technique	4-wire	
Analogue output function	420 mA	
[Us] rated supply voltage	1224 V DC with reverse polarity protection	
Electrical connection	Male connector M12 4 pins	
[Sd] sensing range	0.171.67 ft (0.0510.508 m)	
Beam angle	6 °	
IP degree of protection	IP67 conforming to IEC 60529	

#### Complementary

Enclosure material	Valox	
Front material	Ероху	<u>.</u>
Thread type	M18 x 1	<u>, i</u>
Supply voltage limits	1028 V DC	
[Sa] assured operating distance	0.171.67 ft (0.0510.508 m) (teach mode)	tien tien tien tien tien tien tien tien
Blind zone	02.01 in (051 mm)	
Transmission frequency	300 kHz	
Repeat accuracy	1.27 %	 ច ខ្មី
		<u></u>

Deviation angle from 90° of object to be detected	-77 °	
Minimum size of detected object	Cylinder diameter 1.6 mm	
Status LED	1 LED (dual colour) setting-up assistance 1 LED (green) supply on 1 LED (yellow) output state	
Current consumption	40 mA	
Maximum switching capacity	10500 Ohm overload and short-circuit protection	
Voltage drop	<1V	
Setting-up	Slope selection using teach button	
Delay first up	100 ms	
Delay response	25 ms	
Delay recovery	25 ms	
Marking	CE	
Threaded length	1.69 in (43 mm)	
Height	0.71 in (18 mm)	
Width	0.71 in (18 mm)	
Depth	3.11 in (79 mm)	
Product weight	0.07 lb(US) (0.033 kg)	

#### Environment

Standards	IEC 60947-5-2	
Ambient air temperature for operation	-4149 °F (-2065 °C)	
Ambient air temperature for storage	-40176 °F (-4080 °C)	
Vibration resistance	+/-1 mm conforming to IEC 60068-2-6 1055 Hz	
Shock resistance	30 gn in all 3 axes 11 ms conforming to IEC 60068-2-27	
Resistance to electrostatic discharge	ge 8 kV level 4 conforming to IEC 61000-4-2	
Resistance to electromagnetic fields	9.14 V/yd (10 V/m) level 3 conforming to IEC 61000-4-3	
Resistance to fast transients 1 kV level 3 conforming to IEC 61000-4-4		

### Ordering and shipping details

Category	22490 - SENSORS-ULTRASONIC (XX5,6)	
Discount Schedule	DS2	
GTIN	00785901928843	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.5	
Returnability	Υ	
Country of origin	US	

### Contractual warranty

	•	
Warranty period	18 months	