



Actual

**Catalog Number:** 540500  
**Product ID:** 7TAH007530R0022  
**UPC Number:** 78620992368  
**Status:** Active

Copper Parallel Splice, Wire Range Min: (1) #400MCM and (3) #6, Max: (1) #250MCM and (13) #6, Circular Mil Range 478,000 - 600,000, Tin Plated

- Accomodates multiple wire sizes from 22 AWG to 500 kcmil for application flexibility. Easy to install with standard compression crimp tools.
- Chamfered barrel ends eliminate high-voltage corona and partial discharge failures. 99.9 percent pure copper for low resistance and high conductivity - tin-plated for corrosion resistance.
- Application Tools: TBM8750M1, TBM8750BSCR

### North American Specifications (UNSPSC)

UNSPSC	39121449 Wire or cable compression splice
IGCC	4669 Wire or cable compression splice
Brand Name	Color-Keyed
Type	Splice Connector
Special Features	Accomodates multiple wire sizes from 22 AWG to 500 kcmil for application flexibility. Easy to install with standard compression crimp tools.
Standard	UL E9809
Material	Copper
Finish	Tin-Plated
Voltage Rating	600V

### Packaging

Inner Quantity	5
Inner Dimensions (inches)	3.5x3x3
Outer Quantity	50
Outer Dimensions (inches)	16.5x8x3.75
Weight Uom	23 lbs. per 100

### Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000404
Technical Drawing / Data Sheet Canada	Available on Website

**For further technical assistance, please contact us...**

ABB Installation Products - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

ABB Installation Products Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)