



Actual

Catalog Number: 540250
Product ID: 7TAH007530R0019
UPC Number: 78620992365
Status: Active

Copper Parallel Splice, Wire Range Min: (1) #3/0 and (4) #8, Max: (1) #3/0 and (8) #8, Circular Mil Range 231,100 - 300,000, Tin Plated

- Accomodates multiple wire sizes from 22 AWG to 500 kcmil for application flexibility. Easy to install with standard compression crimp tools.
- Chamfered barrel ends eliminate high-voltage corona and partial discharge failures. 99.9 percent pure copper for low resistance and high conductivity - tin-plated for corrosion resistance.
- Application Tools: TBM8750M1, TBM8750BSCR

North American Specifications (UNSPSC)

UNSPSC	39121449 Wire or cable compression splice
IGCC	4669 Wire or cable compression splice
Brand Name	Color-Keyed
Type	Splice Connector
Special Features	Accommodates multiple wire sizes from 22 AWG to 500 kcmil for application flexibility. Easy to install with standard compression crimp tools.
Standard	UL E9809
Material	Copper
Finish	Tin-Plated
Voltage Rating	600V

Packaging

Inner Quantity	25
Inner Dimensions (inches)	4x3x4
Outer Quantity	250
Outer Dimensions (inches)	21.3x8.3x3.1
Weight Uom	8.5 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000404
Technical Drawing / Data Sheet Canada	Available on Website

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com