



Actual

Catalog Number: 540040
Product ID: 7TAH007530R0007
UPC Number: 78620992364
Status: Active

Copper Parallel Splice, Wire Range Min: (3) #2, Max: (1) 1/0 and (3) #4, Circular Mil Range 190,000 - 231,100, Length 0.77 Inches (19.56mm), O.D. 0.766 Inches (19.46mm), I.D. 0.629 Inches (15.98mm), Tin Plated

- Accomodates multiple wire sizes from 22 AWG to 500 kcmil for application flexibility. Easy to install with standard compression crimp tools.
- Chamfered barrel ends eliminate high-voltage corona and partial discharge failures. 99.9 percent pure copper for low resistance and high conductivity - tin-plated for corrosion resistance.
- Application Tools: TBM8750M1, TBM8750BSCR

North American Specifications (UNSPSC)

| | |
|------------------|--|
| UNSPSC | 39121449 Wire or cable compression splice |
| IGCC | 4669 Wire or cable compression splice |
| Brand Name | Color-Keyed |
| Type | Splice Connector |
| Special Features | Accomodates multiple wire sizes from 22 AWG to 500 kcmil for application flexibility. Easy to install with standard compression crimp tools. |
| Standard | UL E9809 |
| Material | Copper |
| Finish | Tin-Plated |
| Voltage Rating | 600V |

Packaging

| | |
|---------------------------|----------------|
| Inner Quantity | 50 |
| Inner Dimensions (inches) | 4x3x4 |
| Outer Quantity | 500 |
| Outer Dimensions (inches) | 21.5x8.8x3.8 |
| Weight Uom | 4 lbs. per 100 |

Documents / Support Tools

| | |
|---------------------------------------|----------------------|
| Technical Drawing / Data Sheet | WSD-000404 |
| Technical Drawing / Data Sheet Canada | Available on Website |

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com