



<b>PERIMALITER®</b> <b>WALLPACK</b> PGM3 GLASS SERIES	Cat.#		 <b>HUBBELL</b> Outdoor Lighting
	Job	Type	

**APPLICATIONS**

- Perimeter lighting for safety and security. High performance with wide lateral spread

**SPECIFICATIONS**

- Cast aluminum door frame with prismatic glass refractor. Door seals to housing gasket with twin Hubbell Gard® captive fasteners
- Die cast aluminum housing allows firm mounting over recessed junction boxes or on flat surfaces for 1/2" surface conduit. Casting dissipates ballast heat for long life. Top hub supplied for field installation of button photo control, ordered separately
- Specular aluminum reflector with kicker panels drive maximum lamp lumens to the refractor prisms. Vertical socket position with these optics provide six to one spacing to mounting height ratio for maximum spacing or better uniformity, greater lumens and lamp life
- PGM features 100-250W pulse start metal halide. Many listings include lamp for contractor convenience; see standard selections below
- Dark bronze 800 Series powder paint finish standard on frame and housing. For optional finishes, black, gray, white and platinum consult factory



	A	B	C	D
<b>PGM3</b>	147/8"	15"	8"	6 <sup>13</sup> /16"
	378 mm	381 mm	203 mm	173 mm

**ELECTRICAL**

- 10kA surge protection (parallel); Automatically takes fixture off-line when device is consumed

**LISTINGS**

- Listed to UL1598 for use in wet locations




**STOCK ORDERING INFORMATION**

Catalog Number	Wattage	Lamp Type	Voltage	Ballast	Lamp Included/Base	Weight lbs. (kg)
<b>Pulse Start Metal Halide</b>						
<b>PGM3-250P-18-BZ</b>	250	PSMH	Quad Tap	CWA-HPF	No/Mog.	27 (12.2)
<b>PGM3-250P-18-BZ-L</b>	250	PSMH	Quad Tap	CWA-HPF	Yes/Mog.	27 (12.2)

Notes: • L - Indicates lamp included with the fixture

**CONFIGURABLE ORDERING INFORMATION**



SERIES	SOURCE/WATTAGE	BALLAST	VOLTAGE	COLOR/FINISH	OPTIONS
<b>PGM3</b> Glass Refractor Wallpack	<b>PULSE START METAL HALIDE</b> 175P 175w 250P 250w <b>HIGH PRESSURE SODIUM</b> 150S 150w 250S 250w	<b>1</b> HX-HPF	<b>5</b> 480V <b>8</b> 120/208/240/277V	<b>DB</b> Bronze <b>BL</b> Black <b>GR</b> Gray <b>WH</b> White <b>PS</b> Platinum Silver	<b>EM</b> Emergency Socket <b>L</b> Lamp included

## ORDERING INFORMATION

### ACCESSORIES - Order Separately

Catalog Number	Description
PBT-1	Photocontrol, button type, 120V
PBT-234	Photocontrol, button type, 208, 240, 277V
PG-PS <sup>1</sup>	Polycarbonate shield for refractor
PG-WG <sup>1</sup>	Wire guard for refractor
PVL3V	Full cut-off visor, formed aluminum, bronze finish

<sup>1</sup> Guard and shield can be used on the same fixture

### REPLACEMENT PARTS

Catalog Number	Description
80033990104	Aluminum/glass front, bronze (glass conversion)



**HUBBELL**  
Outdoor Lighting

Hubbell Outdoor Lighting • 701 Millennium Boulevard • Greenville, SC 29607 • Phone: 864-678-1000  
Due to our continued efforts to improve our products, product specifications are subject to change without notice.

© 2017 HUBBELL OUTDOOR LIGHTING, All Rights Reserved • For more information visit our website: [www.hubbelloutdoor.com](http://www.hubbelloutdoor.com) • Printed in USA

PGM-SPEC 5/17