



BURNDY Catalog Number
UPC Number
Description
Status

YGL2C2
 7818102200099
 6-2 TO 6-2 GRD GRID/ROD
 Active

Web Use
 BURNDY Product Line

Length (in)
 B Length (in)
 BB - Length (in)

Dimensional
 2.50
 0.75
 0.75

Product Description
 Prefilled (Oxide Inhibitor)
 Type of Oxide Inhibitor

General
 Copper Compression Cross Grid
 Connector, 6 AWG (Sol.) - 2 AWG
 (Str.), 6 AWG (Sol.) - 2 AWG (Str.)
 Y

Rated for Direct Burial
 UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Other
 Penetrox E
Approvals / Certifications
 Y
 Y
 Y
 Compliant
 N
 N
 UL467,IEEE 837

Rod Size (Side A) - Range
 Rod Size (Side B) - Range
 Rebar Size (Side B) - Range
 Copper Solid Size (Side A) - Range
 Copper Str Size(Side B) - Range
 Copper Str Size (Side A) - Range
 CopperSolid Size (Side B) - Range
 Rebar Size (Side A) - Range

Conductor(s)
 1/2 in-5/8 in
 N/A
 N/A
 6 AWG-2 AWG
 6 AWG-2 AWG
 6 AWG-2 AWG
 6 AWG-2 AWG
 N/A

Type of Plating
 Plated (Yes or No)
 Product Material

Physical
 Unplated
 N
 Copper

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175