




**BURNDY Catalog Number** YGL34C34  
**UPC Number** 7818102200544  
**Description** 250-500 TO 250-500 GRD G  
**Status** Active



**Web Use**  
 BURNDY Product Line



Length (in) 2.50  
 B Length (in) 1.10

**Dimensional**

2.50  
 1.10

**General**

Copper Compression Cross Grid Connector, 250 kcmil - 500 kcmil or 5/8" - 3/4" Ground Rod or # 5 - 6 Rebar, 250 kcmil - 500 kcmil  
 Y

**Product Description**

**Prefilled (Oxide Inhibitor)**

**Other**

Penetrox E

**Approvals / Certifications**

**Type of Oxide Inhibitor**

Y

**Rated for Direct Burial**

Y

**UL Listed**

Y

**CSA Certified**

Y

**ROHS Compatible**

Compliant

**UL Recognized**

N

**CULUS**

N

**Industry Standards**

UL467,IEEE 837

**Conductor(s)**

**Rod Size (Side A) - Range**

5/8 in-3/4 in

**Rod Size (Side B) - Range**

N/A

**Rebar Size (Side B) - Range**

N/A

**Copper Solid Size (Side A) - Range**

N/A

**Copper Str Size(Side B) - Range**

250 kcmil-500 kcmil

**Copper Str Size (Side A) - Range**

250 kcmil-500 kcmil

**CopperSolid Size (Side B) - Range**

N/A

**Rebar Size (Side A) - Range**

5 -6

**Physical**

**Type of Plating**

Unplated

**Plated (Yes or No)**

N

**Index Number**

1011

**Product Material**

Copper

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175