



BURNDY Catalog Number
UPC Number
Description
Status

YA322LN
 781810505266
 400 CU 2-HOLE SHORT NEMA
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle	Straight
Length (in)	4.88
Tongue Type	Standard
Barrell Style	Chamfered, Skived
Bolt Hole Size (in)	0.52
Barrel Type	Standard
Thickness	0.19
B Length (in)	1.19
Pad Width (in)	1.40
E - in	1.75
Strip Length	1-1/4

General

Number of Holes	2
Product Description	Cu Comp Terminal Code Cond, Bvl Entry, 2 Hole/W/InspWindow, 400 kcmil Str Code, 400 Navy, 600 V-35 kV, 1/2" Stud, 1.75" Spacing, Std bbl, Blue, 19 or 470 Index

Conductor(s)

Flex (Class G) Size - Range	N/A
Flex (Class H) Size - Range	N/A
Flex (Class I) Size - Range	N/A
Copper Solid Size (Range)	N/A
DLO Size (Range)	N/A
Copper Stranded (Range)	400 kcmil

Physical

Type of Plating	Tin - Electro Plated
Bolt Hole Size	1/2
Color Code	Blue
Plated (Yes or No)	Y
Index Number	19,470
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175