



BURNDY Catalog Number
UPC Number
Description
Status

YA38L2NTCFX
 7818105217244
 CU HYLUG-500 FLEX-NEMA
 Active

Web Use
 BURNDY Product Line

Dimensional

Tongue Angle Straight
 Length (in) 5.35
 Tongue Type Standard
 Barrell Style Chamfered,Skived
 Bolt Hole Size (in) 0.52
 Barrel Type Standard
 Thickness 0.27
 B Length (in) 1.45
 Pad Width (in) 1.84
 E - in 1.75
 Strip Length 1-7/16

General

Number of Holes 2
 Product Description Copper Compression Lug, 2 Hole
 w/ Inspection Window, 535.3 Flex,
 1/2" Stud, 1-3/4" Stud Hole
 Spacing, Short Barrel, Tin Plated

Conductor(s)

Flex (Class G) Size - Range 500 kcmil
 Flex (Class H) Size - Range 500 kcmil
 Flex (Class I) Size - Range 500 kcmil
 Copper Solid Size (Range) N/A
 DLO Size (Range) 535.3 (1325/#24) DLO
 Copper Stranded (Range) N/A

Physical

Type of Plating Tin
 Bolt Hole Size 1/2
 Color Code Pink
 Plated (Yes or No) Y
 Index Number L99
 Product Material Copper

Approvals / Certifications

UL Listed Y
 CSA Certified Y
 ROHS Compatible Compliant
 UL Recognized N
 CULUS N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM

Monday - Friday

Phone: 800-346-4175