



BURNDY Catalog Number
UPC Number
Description
Status

KPA34
 7818103569511
 SCRULUG 4/0-500, 1/2 HOL
 Active

Web Use
 BURNDY Product Line

Dimensional

Length (in)	3.32
Thickness (in)	1/5
Height (in)	2.44
Stud Size (in)	1/2
Thickness	0.20
D - in	1.38
Pad Width (in)	1.38
N (in)	0.75

General

Number of Holes	1
Number of Screws	1
Product Description	Copper Terminal, 1 Hole, 4/0 AWG (Str)-500 kcmil, 1/2" Stud, 1 Screw, Tin Plated

Conductor(s)

Copper Solid Size (Range)	N/A
Copper Stranded (Range)	4/0 AWG-500 kcmil

Physical

Screw Type	Hexagonal Bolt
Installation Torque	375
Type of Plating	Tin
Connector Type	Terminal
Plated (Yes or No)	Y
Product Material	Copper

Approvals / Certifications

UL Listed	Y
CSA Certified	Y
Rated for Direct Burial	N
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175