



Family

Catalog Number: TNF18-4MB-XV
Product ID: 7TAI029350R0154
UPC Number: 72849414490
EAN Number: 05414363492153
Status: Active

Fully Insulated Nylon Male Bullet Disconnects for Wire Range 22-16 , Red

- Fully Insulated. Metal Insulation Sleeve. Molded Insulator. Internal Barrel Serrations. Funnel Entry.
- Application Tools: WT112M, CM2000C

North American Specifications (UNSPSC)

UNSPSC	39121447 Wire terminal disconnect
IGCC	4667 Wire terminal disconnect
Brand Name	Catamount
Type	Disconnects
Special Features	Fully Insulated. Metal Insulation Sleeve. Molded Insulator. Internal Barrel Serrations. Funnel Entry.
Standard	UL E9809
Material	Brass with Copper Sleeve
Color	Red
Insulation	Nylon/Polyamide

European Specifications (ETIM)

ETIM	EC000516 Round or flat plug/receptacle
Model	Plug
Insulation	Fully Insulated
Colour insulation	Red
Material insulation	PA

Packaging

Inner Quantity	75
Inner Dimensions (inches)	50.59x3.29x3.11
Outer Quantity	900
Outer Dimensions (inches)	10.5x10x8
Weight Uom	5 lbs. per 1000

Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website

For further technical assistance, please contact us...

ABB Installation Products - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

ABB Installation Products Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com