



BURNDY Catalog Number	YA322NFXB
UPC Number	7818100399155
Description	BELLED LUG-300 FLEX-NEMA
Status	Active

Web Use
BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	6.04
Tongue Type	Standard
Barrell Style	Belled
Bolt Hole Size (in)	0.52
Barrel Type	Long
Thickness	0.19
B Length (in)	2.32
Pad Width (in)	1.40
E - in	1.75
Strip Length	2-1/4
General	
Number of Holes	2
Product Description	Cu Comp Terminal Flex
	Cond(Telecom), 2
	Hole/W/O/InspWindow, 313.1
	kcmil(775/#24)DLO, 600 V-35 kV,
	1/2" Stud, 1.75" Spacing, Lng bbl,
	Belled End, Red, 18 Index
Conductor(s)	
Aircraft Cable Size (Range)	N/A
Flex (Class H) Size - Range	313.1
Flex (Class I) Size - Range	313.1
Copper Solid Size (Range)	N/A
DLO Size (Range)	313.1 (775/#24)
Navy Cable Size (Range)	N/A
Copper Stranded (Range)	300 kcmil
Flex (Class G) Size - Range	313.1
Flex (Class M) Size - Range	313.1
Physical	
Type of Plating	Tin
Bolt Hole Size	1/2
Color Code	Red
Plated (Yes or No)	Y
Index Number	18
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175