

YSV6CFXB

by Burndy
Catalog ID: YSV6CFXB

Prop 65 Notice

Telecom Belled Copper Hylink, #6 Str.(61/24) #6 AWG, 30 Navy, 2.62 IN L, Cable Strip Length: 1-5/16 IN.

Features: Long Barrel Length: High Voltage Terminations, Four (4) Center Conductor Stops: Provides A Center Wire Stop For Proper Conductor Insertion, High Pull Out Force: Provides Added Security For Greater Mechanical And Electrical Properties, Belled Cable Entry: A Funnel Type Entry Provide Easy Insertion Of Extra Flexible Cables Plus Offers Mechanical Strain Relief For Individual Strands, Color Code: Blue, Oil Stop: No, Tapered End: No, Dieless Tools (number Of Crimps): Y81KFT, Y81KFTMBH, PAT81KFT-18V Tool, (1), Die Index: 7 Element A, Tools, Die Set Catalog Number, And (number Of Crimps): Mechanical: Y1MR, Y2MR Tool, (2), Y1MRTC Tool, Y35, Y39, Y750 Tool, U5CRT Die, (2), Y46 Tool, U5CRT Die With PUADP-1 Adapter, (2), Conductor Type: Flexible Copper, Wire Strip Length: 1-5/16 IN



Product Details

General

| | |
|------------------------|---------------------------------|
| Application | For Higher voltage applications |
| Color Code | Blue |
| Connector Type | Splice |
| Die Index | 7 |
| Feature - Barrel Style | Belled |
| Feature - Barrel Type | Long |
| Material | Copper |
| Plated | Y |
| Plating Type | Tin |
| Sub Brand | HYLINK |
| Trade Name | HYLINK™ |
| Type | Splice |
| UPC | 781810041505 |

Dimensions

| | |
|-----------------------------------|-----------|
| Dimension - B Length fraction | 1-3/16 in |
| Dimension - B Length inch | 1.22 in |
| Dimension - D inch | 0.37 in |
| Dimension - L Length Overall mm | 67 mm |
| Dimension - Length Overall inch | 2.62 in |
| Dimension - Outside Diameter inch | 0.31 in |
| Dimension - Strip Length inch | 1-5/16 in |

Conductor Related

| | |
|--------------------------------|----------------|
| Conductor - Copper DLO Size | 6 (61/#24) DLO |
| Conductor - Copper Flex G Size | 6 AWG |

| | |
|---|--|
| Conductor - Copper Flex H Size | 6 AWG |
| Conductor - Copper Flex I Size | 6 AWG |
| Conductor - Copper Flex K Size | 6 AWG |
| Conductor - Copper Flex M Size | 6 AWG |
| Conductor - Copper Solid Size | 6 AWG |
| Conductor - Copper Str Compact Size | 6 |
| Conductor - Copper Str Compact Size Range | 6 |
| Conductor - Copper Str Navy Size | 30 (19) |
| Conductor - Copper Str Size | 6 AWG |
| Conductor Type | <ul style="list-style-type: none"> • CU C Solid-Size • CU C Str-Size |

Certifications and Compliance

| | |
|------------------------------------|-----|
| Certification - CSA Approved | Yes |
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

Logistics

| | |
|-----------------------|----|
| Minimum Pack Quantity | 50 |
|-----------------------|----|

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)