



BURNDY Catalog Number
UPC Number
Description
Status

YE38P71X142FX
 7818100377444
 CU PIN TERM 550KCMIL 535 DLO
 Active

Web Use
 BURNDY Product Line

Dimensional

Pin Size (Equivalent)	500 kcmil
Length (in)	5.30
B Length (Fraction)	3-5/16
B Length (in)	3.29
Pin Size (Equivalent) - Cross	0.71 in. - 500 kcmil
Diameter (in) - Total	0.71
P	1.42
Strip Length	3-3/8

General

Product Description
 Copper Compression Pin Adapter,
 535.3 Flex, 0.71" Plug Dia,
 1.42" Plug Length, Tin Plated

Conductor(s)

Flex (Class C) Size - Range	N/A
Flex (Class H) Size - Range	550 Kcmil
Flex (Class I) Size - Range	550 Kcmil
Copper Compact Size (Range)	N/A
DLO Size (Range)	535.3 (1325/#24) DLO
Flex (Class G) Size - Range	550 Kcmil
Flex (Class M) Size - Range	N/A

Physical

Plated (Yes or No)	Y
Type of Plating	Tin - Electro Plated
Index Number	L99
Product Material	Copper

Approvals / Certifications

UL Listed	N
CSA Certified	N
ROHS Compatible	Compliant
UL Recognized	N
CULUS	Y

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM

Monday - Friday

Phone: 800-346-4175