



BURNDY Catalog Number
UPC Number
Description
Status

KA252TC38
 7818100340577
 KALUG (2) 3/8 BOLTS 1 C
 Active

Web Use
 BURNDY Product Line

Dimensional	
Size (Hex) or Size (Bolt)	1/2
Length (in)	2.69
Thickness (in)	3/23
Height (in)	0.94
B Length (Fraction)	20/29
Hole Size (Fraction)	27/64
Stud Size (in)	3/8
Thickness	0.13
Size (Hex) or Size (Bolt) - in	0.50
B Length (in)	0.69
Pad Width (in)	0.75
N (Fraction)	3/8
N (in)	0.38
Hole Size (in)	0.42
Length (Fraction)	2-13/16
Height (Fraction) (in)	15/16
General	
Product Description	Cast Copper Alloy KA-Lug, 4 Str. - 1/0 Str., 3/8
Conductor(s)	
Copper Solid Size (Range)	N/A
Copper Stranded (Range)	4 AWG-1/0
Physical	
Screw Type	Allen
Type of Hardware	1 / 2 "
Installation Torque	200
Type of Plating	Unplated
Connector Type	Terminal
Plated (Yes or No)	N
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	N
ROHS Compatible	Exempt
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175