



Powering Business Worldwide

pe.eaton.com

M22 Non-Illuminated Emergency Stop Contact Block

M22-KC10-B100

UPC:786685278193

Dimensions:

- **Height:** 1.03 IN
- **Length:** 1.46 IN
- **Width:** 1.18 IN

Weight:3.4 LB

Notes:All NC contact blocks are positively driven contact

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Type:** Contact Block
- **Actuator:** Base, Screw
- **Color:** Black
- **Contact Configuration:** NO
- **Environmental Rating:** IP66, NEMA 4X, 13
- **Size:** 22.5 mm
- **Series:** M22

Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [M22 Operators and Accessories](#)
- [M22 Pilot Devices](#)
- [Eaton Specification Sheet - M22-KC10-B100](#)

Certifications:

- CCC Marked
- CSA Certified
- Lloyd's Register Certified



Product compliance:

- Bureau Veritas
- GoST-R
- CE Marked

© 2016 Eaton. All rights reserved.