



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## M22 Non-Illuminated Emergency Stop Contact Block

**M22-CKC01**

**UPC:**786685278070

### Dimensions:

- **Height:** 1.54 IN
- **Length:** 1.03 IN
- **Width:** 1.18 IN

**Weight:**.034 LB

**Notes:**All NC contact blocks are positively driven contact

### Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Specifications:

- **Type:** Contact Block
- **Actuator:** Base, Spring-cage
- **Color:** Black
- **Contact Configuration:** NC
- **Environmental Rating:** IP65
- **Size:** 22.5 mm
- **Series:** M22

### Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [M22 Operators and Accessories](#)
- [M22 Pilot Devices](#)
- [Eaton Specification Sheet - M22-CKC01](#)
- [Global Data Sheet - M22-CKC01](#)

### Certifications:

- CSA Certified
- CCC Marked



- Lloyd's Register Certified

**Product compliance:**

- CE Marked
- Bureau Veritas
- GoST-R

---

© 2016 Eaton. All rights reserved.