



GE  
Lighting

### 78627 - GE432MAX-N/ULTRA

#### GE LFL UltraMax™ Electronic High Efficiency Multivolt Instant Start Ballast

- Energy saving high efficiency instant start electronic ballast (> 90%)
- Multi-Voltage Technology handles voltage from 120 to 277V
- UL Type CC Rating provides protection against arcing in electrical devices.
- Anti-Striation Control for better light quality, with no striations.
- UL 55C Ambient Rating - HighTemperature Protection Circuit
- Cold temperature -20F Minimum Starting Temperature



#### CAUTIONS & WARNINGS

##### Warning

- Risk of Electric Shock
  - Properly ground ballast and fixture.
  - Turn power off before servicing--see instructions.

#### GENERAL CHARACTERISTICS

Lamp Type	Fluorescent -
Bulb	Electronic
Ballast Type	High Efficiency Multivolt
	Instant Start
Starting Method	Instant start
Lamp Wiring	Parallel
Line Voltage Regulation (+/-)	10.0 %
Ambient Temperature (MAX)	40.0 °C
Ballast Factor	Normal
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Additional Info	Anti-striation control/Auto-restart/Thermally protected

#### ELECTRICAL CHARACTERISTICS

Supply Current Frequency	50.0 Hz
--------------------------	---------

#### DIMENSIONS

Weight	1.1 lb
Exit Type	
Remote Mounting Distance	18.0 ft
Remote Mounting Wire Gauge	18.0 AWG

#### PRODUCT INFORMATION

Product Code	78627
Description	GE432MAX-N/ULTRA
Standard Package	Case
Standard Package GTIN	10043168786277
Standard Package Quantity	10
Sales Unit	Standard Pack
No Of Items Per Sales Unit	1
No Of Items Per Standard	10
Package	
UPC	043168786270