



* Representative image

Veri*Lite PDI Insulator, 15kV

by OHIO BRASS
Catalog ID: 8010150215

Silicone Polymer 15kV Deadend Insulator PDI-15

- Weathersheds:
- These Veri*Lite Insulators are manufactured with silicone rubber with Ohio Brass proprietary compound, the same proven material used in Quadri*Sil Transmission Insulators.

Insulators are available with other ANSI and IEC end fittings. Please refer to the catalog for the configurable options available.

Product Details

General

Application	Deadend
Cantilever Bending Strength - Routine	7500
Fitting - Ground/Base	Clevis
Fitting - Live Line End	Tongue
Insulator Type	DS15
Material	Silicone Polymer
Material - End Fitting	Steel
Material - Pin (Cotter)	Stainless Steel
Number of Sheds	4
Shed Style	Uniform
Strength Rating - Ultimate	15000 lb
Tensile Strength	15 K
Tensile Strength - Routine	7500
Type	PDI-15
UPC	096359433446

Dimensions

Diameter - Shed(s)	3.6
Length - Effective	12.5 in
Rod Diameter	0.625
Thickness - Housing	0.100
Weight	2.37 lb

Electrical Ratings

Arc Distance - Dry	8
Creep and Leakage Distance	16 IN (406 mm)
Critical Impulse Flashover (CIFO) - Negative	160
Critical Impulse Flashover (CIFO) - Positive	140
Flashover Voltage - 60 Hz Dry	110
Flashover Voltage - 60 Hz Wet	75

Voltage - Line	15000 V
----------------	---------

Certifications and Compliance

Industry Standard(s)	ANSI DS-15
----------------------	------------

Logistics

Pallet Quantity	480 EA
Standard Package	15

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscsc@hubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com