



* Representative image

Veri*Lite PDI Insulator, 35KV

by OHIO BRASS
Catalog ID: 8010350215

Silicone Polymer 35kV Deadend Insulator PDI-35

- Weathersheds:
- These Veri*Lite Insulators are manufactured with silicone rubber with Ohio Brass proprietary compound, the same proven material used in Quadri*Sil Transmission Insulators.

Insulators are available with other ANSI and IEC end fittings. Please refer to the catalog for the configurable options available.

Product Details

General

Application	Deadend
Cantilever Bending Strength - Routine	7500
Fitting - Ground/Base	Clevis
Fitting - Live Line End	Tongue
Insulator Type	N/A
Material	Silicone Polymer
Material - End Fitting	Steel
Material - Pin (Cotter)	Stainless Steel
Number of Sheds	8
Shed Style	Uniform
Strength Rating - Ultimate	15000 lb
Tensile Strength	15 K
Tensile Strength - Routine	7500
Type	PDI-35
UPC	096359433484

Dimensions

Diameter - Shed(s)	3
Length - Effective	25.0 in
Rod Diameter	0.625
Thickness - Housing	0.148
Weight	2.94 lb

Electrical Ratings

Arc Distance - Dry	20
Creep and Leakage Distance	33 IN (838 mm)
Critical Impulse Flashover (CIFO) - Negative	360
Critical Impulse Flashover (CIFO) - Positive	325
Flashover Voltage - 60 Hz Dry	200
Flashover Voltage - 60 Hz Wet	160

Voltage - Line	35000 V
Withstand Voltage - 60 Hz Dry	170
Withstand Voltage - 60 Hz Wet	130

Certifications and Compliance

Industry Standard(s)	ANSI
----------------------	------

Logistics

Pallet Quantity	300 EA
Standard Package	15

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscsc@hubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com