

Interactive @Catalog

Catalog Home

Product Datasheet

ANDERSON FARGO

SEDA1813SSAC -- Compression Deadend



Compression Deadend, Conventional 2-Die, Single Tongue, for ACSS 477.0 kcmil 30/7, With Terminal

Product Specifications Compression Deadend Assemblies **Category Image** Aluminum Conventional (two die) AAC, ACSR, & ACSS Conductor Series Image (Comp Assy) **PDF Catalog Page** Click HERE to view the web page. **Terminal Option** With Style Conventional 2-Die, Single Tongue **Outside Diameter** 0.883 in Compression **Type Material** Aluminum/Steel **Compression Method** Conventional (2 die system) **Aluminum Die** 24AH **Steel Die** 12SH **Minimum Press (Tons)** 60 **Voltage Application** Std **Inhibitor Loaded** No **Body Material** Seamless Extruded Aluminum Alloy **Eye Material** Galvanized Forged Steel

Terminal Material	Seamless Extruded Aluminum Alloy
Hardware Material	Aluminum Alloy
Length before Compression	18.6 in (472 mm)
Dimension A	2.5 in (63 mm)
Dimension B	1.0 in (25 mm)
Dimension C	0.55 in (14.0 mm)
Pad Width	2.5 in (64 mm)
Bolt Holes	2
Conductor Range Minimum - Maximum	ACSS 477.0 kcmil (30/7) Hen
Standard Package	1

Notes

To specify double-tongue deadend, change first character of Catalog Number from S to D.

Compressed Product Number

SEDA1813SSAC



Dimensions

Catalog Home



Warranty Info | **Trademarks** | **Terms of Use**

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.